

Thermal Receipt Printer : BT300Plus

Reliable and Advanced

SIMPLE ...BETTER...FASTER



300mm/sec ultra high speed

OPOS Support



Technical Specifications

Model BT300Plus

Print Method	Direct Thermal line
Dot density	576dot/line & 512dot/line
Print speed	300 mm/sec
Print width	80 ±0.5mm
Interface	Serial+USB+Ethernet OR USB+Parallel
Paper thickness	0.06~0.08mm
Print command	compatible with ESC/POS
Paper loading	easy loading
Driver	Windows XP/2003/7/8, Linux, OPOS
Barcode type	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODEBAR/CODE128/ CODE93
Power adapter	DC24V/2A
Cash drawer	DC24V/1A
Mechanism	150KM
Auto cutter	Partial, 1.5 million cuts
Work environment	Temperature 0~45°C ,humidity: 10~80%
Storage environment	temperature -10~60°C ,humidity: 10~90%

Kitchen printing and network printing supported | dimension: 139x181x127mm(w x l x h)

Product By

Borse Technologik, Pune, India

Email us : info@borse.co.in

Call us : 09960112223



Our Other Products

Barcode Scanner | Barcode Printer | Mobile Printer | POS Paper Roll | Barcode Labels & Ribbon